



AS-7100ULS

AS-7100ULS is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. It integrates a single port VGA KVM switch, monitor, keyboard & mouse into 1U height and is used to control one computer. A value keyboard with number block and the integrated touchpad are completing the external design. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit. **Depth: 410mm** (without handle)

FEATURES

- * Front LCD Console + DB 37pins cable in **short total depth 410mm**, supports PS.2/USB
- * Can be connected with different KVM modules, for example with 4/8/16 ports (VGA/CAT5)
- * an USB 1.1 port on the frontside, for external mouse or keyboard
- * high and clear resolution 1280 x 1024 (60Hz)

KEYBOARD VERSIONS

Available in following versions: German (DE), US-English (US), British-English (UK), French (FR), Spanish (SP), Italian (IT), Turkish (TR), Swedish/Finnish (SWE/FI), Swiss (CH) and Russian (RU)

**** The corresponding cables are included with delivery. ****

**** Alternatively available with 3.0m cable against surcharge - please feel free to contact us. ****

Specifications

Type		AS-7100ULS
Computer Connection (direct/max)		1
CPU Port Selection		--
IP Remote Control		No --
LCD monitor	Monitor type	17" SXGA color TFT-LCD
	Ratio	4:3
	Visible square	337.920(H) × 270.336(V)
	Resolution(max)	1280 x 1024 @ 60HZ
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.264 x 0.297mm
	LCD MTBF	100,000 hours
	Input power	DC 12 V
Connectors	DB 37pin Rear*	1 x PS/2 female (purple, green)
		1x Kombi-USB
		1 x HDB-15 VGA male (blue)
	USB Front	1 x USB for external mouse or keyboard
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatible IBM/AT	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal (black)
Rail system		Single Rail
Gross weight		15.0 kg
Dimensions (installation depth)		407.5 x 450 x 44.5mm
Dimensions (with handle)		462.6 x 450 x 44.5mm
Rack installation depth		410mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C

* The needed combo cable is included with delivery.