AS-9116TLD

AS-9116TLD is a 19“ dual rail Monitor, Keyboard-Drawer with LED Backlight. It integrates a 16-port CAT.5 KVM switch, monitor, keyboard & mouse into 1U height and is used to control up to 16 computers. An ultra thin keyboard with number block and the integrated touchpad are completing the external design. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit.

Because of the combination of design and the dual rail structure, the monitor and the keyboard can be pulled out independently. In case of pulling the whole console out of the server cabinet the power turns off automatically. Pushing it back to the cabinet, the power turns on again. Depth 700.0mm

FEATURES

* compatibility to PS.2 / USB standard interface
* supports VGA, SVGA and XVGA input
* 19” LED screen with high brightness, high and clear resolution
* suitable for 19’’ standard rack installation and metal structure
* ultra thin keyboard with keypad
* mouse touchpad with two function button.
* front panel with lock to prevent damage by accident
* can be totally pulled out from the cabinet and the LCD screen can be turned on to 120°
* can be connected with different KVM modules, for example with 4/8/16 ports (VGA/CAT5)
* automatic power on/off when pulling the console out / in
* accords with DDC, DDC2, DDCB and VESA standard
* easy use of the OSD menu

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)
Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)
* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

** The corresponding dongles (16x KD-DON-USB) are **included** with delivery. **

Specifications

Type		**AS-9116TLD**	
Computer Connection (direct/max)		16 / 256	
CPU Port Selection		Front panel buttons / OSD menu	
IP Remote Control		optional	- -
LCD monitor	Monitor type	19" Wide AHVA TFT-LCD	
	Ratio	4:3	
	Visible square	376.32(H) x 301.06(V)mm	
	Resolution(max)	1280 x 1024 (native) 60Hz	
	Support Color	16.7M colours (True 8-bit)	
	White Luminance	250 cd/m2 (Typ.)	
	contrast	1000:1 (Typ)	
	Back light	LED	
	Pixel Pitch	294x294um	
	LCD MTBF	100.000 hours	
	Input power	DC 12 V	
Connectors	PC connectors	16 x RJ45	
		2 x USB (rear)	
Dongle Connectors	Keyboard, mouse	KT-150 (1 x USB male)	
	Video	1 x HDB-15 male (blue)	
	Network Port	RJ45 connector	
	Distance	100m(STP/UTP); dongle to PC	
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)	
	Compatible IBM/AT	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.	
	Using life	>1,000,000 times	
Mouse	Type	Touch Pad	
	X/Y resolution	>1000dots/inch (40x40/mm)	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF >100.000 hours 25°C	
Housing		Metal (black)	
Rail system		Dual Rail	
Gross weight		19.0 kg	
Dimensions (installation depth)		645 x 443 x 42 mm	
Dimensions (with handle)		700 x 443 x 42 mm	
Rack installation depth		645mm - 900mm (min/max adjustable)	
Operating / Storage Temp		-10 - 50°C / -20 - 60°C	