



AS-9116ULD-IP

AS-9116ULD-IP is a 19" dual rail Monitor, Keyboard-Drawer with LED Backlight and integrated IP module. It combines a 16-port VGA KVM switch, monitor, keyboard & mouse into 1U height and is used to control up to 16 computers. An ultra thin keyboard with number block and the integrated touchpad are completing the external design. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit.

Because of the combination of design and the dual rail structure, the monitor and the keyboard can be pulled out independently. In case of pulling the whole console out of the server cabinet the power turns off automatically. Pushing it back to the cabinet, the power turns on again. Depth 700.0mm

PARTICULARITY

This version has an integrated IP module (RJ45 Port), which realizes the function of "remote control".

FEATURES

- * compatibility to PS.2 / USB standard interface
- * supports VGA, SVGA and XVGA input
- * 19" LED screen with high brightness, high and clear resolution
- * suitable for 19" standard rack installation and metal structure
- * ultra thin keyboard with keypad
- * mouse touchpad with two function button.
- * front panel with lock to prevent damage by accident
- * can be totally pulled out from the cabinet and the LCD screen can be turned on to 120°
- * can be connected with different KVM modules, for example with 4/8/16 ports (VGA/CAT5)
- * automatic power on/off when pulling the console out / in
- * accords with DDC, DDC2, DDCB and VESA standard
- * easy use of the OSD menu

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* ATTENTION: Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables (16x KD-KAB-102-4) are included with delivery. ****

Specifications

Type		AS-9116ULD-IP
Computer Connection (direct/max)		16 / 256
CPU Port Selection		Front panel buttons / OSD menu
IP Remote Control		Yes KI-4101
LCD monitor	Monitor type	19" Wide AHVA TFT-LCD
	Ratio	4:3
	Visible square	376.32(H) x 301.06(V)mm
	Resolution(max)	1280 x 1024 (native) 60Hz
	Support Color	16.7M colours (True 8-bit)
	White Luminance	250 cd/m2 (Typ.)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	294x294um
	LCD MTBF	100.000 hours
	Input power	DC 12 V
Connectors	PC connectors	16 x HDB-15 male (blue)
		2 x USB (rear)
IP Port	Net Connection	1x RJ45 Port
	Reset	1x LED
	Default	1x LED
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatible IBM/AT	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >100.000 hours 25°C
Housing		Metal (black)
Rail system		Dual Rail
Gross weight		19.0 Kg
Dimensions (installation depth)		645 x 443 x 42mm
Dimensions (with handle)		700 x 443 x 42mm
Rack installation depth		645mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C