



AW-1701HD

AW-1701HD is a 17,3" FULL HD /LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant HD images and Monitoring to unprecedented quality. AW-1701HD sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad, the integrated DVI and VGA Input and 3 Front USB connectors are completing the external design. The casing conforms the 1U Standard, is easily installed and mountable with the included mounting kit. Depth 640mm

FEATURES

- * Adjustable depth from 640 mm up to 1140 mm tread depth
- * DVI-I und VGA Input, USB for Keyboard und Touchpad
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Support DOS, Windows Series /Server 2008 / Server 2013, Linux, MacOS, etc.
- * Continuously adjustable angle from 0 to 105° over high quality unique torque hinges
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * High graphic resolution, up to 1920 x 1080 with 60Hz DDC, DDC2 and DDC2B

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cable (1x KAB-102DVI) is included with delivery. ****

**** Optional compatibility to HDMI devices with KAB-102-HDMI-DVI ****

Specifications

Type		AW-1701HD
Computer Connection		1x DVI-I, 1x VGA, 3x USB 2.0 (Hub) Type A (Front)
CPU Port Selection		- -
Cable Connectors	Keyboard / Mouse	2 x USB Type A (Rear)
	Video	1x DVI-I, 1x VGA
LED's	Operation	1x green
	Num Lock	1x green
	Shift Lock	1x green
	Roll	1x green
LCD monitor	monitor	17,3" LCD monitor
	visible square	214.0 mm (H) * 380.0 mm (V)
	Resolution(max)	1920 x 1080 (DVI Single Link)
	Support Color	16.2 M / 262K colors
	White Luminance	300 cd/m ²
	contrast	700:1 (Typ)
	Back light	LED
	Pixel Pitch	0.264 mm (H) x 0.264 mm (V)
	LCD MTBF	50,000hours
	Input power	DC 12 V
Keyboards	keyboard	Standard (DE) with Num Lock, 104 signs
	Compatible IBM/AT	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.
	Emulation	PS/2 & USB
	Using life	>1,000,000 times
Mouse	X/Y resolution	1000dots/inch 40x40/mm
	Emulation	PS/2 & USB
	Os support	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF>60,000hours 25 °C
Housing		High performance steel (black), RAL 9005
Dimensions	without drawer handle	64,00 x 43,6 x 4,4cm (19" / 1U)
	with drawer handle	67,80 x 43,6 x 4,4cm (19" / 1U)
Rack installation depth		640mm - 1140mm (adjustable)
Weight / Weight incl. Packaging		12.9kg (incl. Mounting Kit) / 17.1kg
Operating/storage Temp		0° - 40°C / -20 - 60°C