



AS-7104TLS

AS-7104TLS is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. Connected by a 4-port Cat.5 KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for four Cat.5 to VGA and USB connectors. A value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

Depth: 611mm

FEATURES

- * Adjustable depth from 555 mm up to 900 mm tread depth
- * Four Cat.5 to VGA and USB connectors
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * high and clear resolution 1280 x 1024 (60Hz)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding dongles (4x KD-DON-USB) are included with delivery. ****

Specifications

| Type | | AS-7104TLS |
|----------------------------------|-------------------|--|
| Computer Connection (direct/max) | | 4 / 64 |
| CPU Port Selection | | Front panel buttons / OSD menu / Hot Key |
| IP Remote Control | | No -- |
| LCD monitor | Monitor type | 17" SXGA color TFT-LCD |
| | Ratio | 4:3 |
| | Visible square | 337.920(H) × 270.336(V) |
| | Resolution(max) | 1280 x 1024 @ 60HZ |
| | Support Color | 16.7M (RGB 6 bit + Hi_FRC) |
| | contrast | 1000:1 (Typ) |
| | Back light | LED |
| | Pixel Pitch | 0.264 x 0.297mm |
| | LCD MTBF | 100,000 hours |
| | Input power | DC 12 V |
| Connectors | PC connectors | 4 x RJ45 port |
| | | 1 x USB for external mouse or keyboard (Front) |
| | | 2 x USB for external mouse or keyboard (Rear) |
| Dongle* | Connector | 1x RJ45 port |
| | Connector 2 | 1x VGA, 1x Kombi-USB |
| Keyboard | Keyboard | Standard 100keys (10 different languages for choose) |
| | Compatible IBM/AT | no limitations |
| | Using life | >1,000,000 times |
| Mouse | Type | Touch Pad |
| | X/Y resolution | >1000dots/inch (40x40/mm) |
| | Using life | >1,000,000 times |
| Power | Power (AC) | ~100V-240V |
| | Using life | MTBF >60,000hours 25 °C |
| Housing | | Metal (black) |
| Rail system | | Single Rail |
| Gross weight | | 16.45 kg |
| Dimensions (installation depth) | | 555 x 450 x 46 mm |
| Dimensions (with handle) | | 611 x 450 x 46 mm |
| Rack installation depth | | 555mm - 900mm (min/max adjustable) |
| Operating / Storage Temp | | -10 - 50°C / -20 - 60°C |
| Humidity | | 0 - 80% no condensation |

* The needed dongles are included with delivery.