



## AS-7108ULS-IP

AS-7108ULS-IP is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. Connected by a 8-port VGA KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for eight VGA to VGA, PS/2 and USB connectors. A value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

**Depth: 611mm**

### PARTICULARITY

This version has an integrated IP module (RJ45 Port), which realizes the function of "remote control".

### FEATURES

- \* Adjustable depth from 555 mm up to 900 mm tread depth
- \* Eight VGA to VGA, PS/2 and USB connectors
- \* compatible with the most KVM-Switches
- \* Support friendly external power supply
- \* Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- \* high and clear resolution 1280 x 1024 (60Hz)

### KEYBOARD VERSIONS

**Available with standard keyboard layouts:** German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

**Optional available against surcharge:** UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

\* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! \*

**\*\* The corresponding cables (8x KD-KAB-102-4) are included with delivery. \*\***

## Specifications

Type		AS-7108ULS-IP	
Computer Connection (direct/max)		8 / 128	
CPU Port Selection		Front panel buttons / OSD menu / Hot Key	
IP Remote Control		Yes	IP module KI-4101
LCD monitor	Monitor type	17" SXGA color TFT-LCD	
	Ratio	4:3	
	Visible square	337.920(H) × 270.336(V)	
	Resolution(max)	1280 x 1024 @ 60HZ	
	Support Color	16.7M (RGB 6 bit + Hi_FRC)	
	contrast	1000:1 (Typ)	
	Back light	LED	
	Pixel Pitch	0.264 x 0.297mm	
	LCD MTBF	100,000 hours	
	Input power	DC 12 V	
Connectors	PC connectors	8 x VGA DB15, Female (blue)	
		1 x USB for external mouse or keyboard (Front)	
		2 x USB for external mouse or keyboard (Rear)	
IP Port	Net Connection	1x RJ45 Port	
	Reset	1x LED	
	Default	1x LED	
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)	
	Compatibility	no limitations	
	Using life	>1,000,000 times	
Mouse	Type	Touch Pad	
	X/Y resolution	>1000dots/inch (40x40/mm)	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF >60,000hours 25 °C	
Housing		Metal ( black )	
Rail system		Single Rail	
Gross weight		17.9 kg	
Dimensions (installation depth)		555 x 450 x 46 mm	
Dimensions (with handle)		611 x 450 x 46 mm	
Rack installation depth		555mm - 900mm (min/max adjustable)	
Operating / Storage Temp		-10 - 50°C / -20 - 60°C	
Humidity		0 - 80% no condensation	

\* The needed dongles are included with delivery.