



AW-1708HD-DVI

AW-1708HD-DVI is a 17,3" FULL HD /LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant HD images and Monitoring to unprecedented quality. AW-1708HD-DVI sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad, the eight integrated DVI / USB Input and 3 Front USB connectors are completing the external design. The casing conforms the 1U Standard, is easily installed and mountable with the included mounting kit. Depth 640mm

FEATURES

- * Adjustable depth from 640 mm up to 1140 mm tread depth
- * DVI-I und USB Input, USB for Keyboard und Touchpad
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Support DOS, Windows Series /Server 2008 / Server 2013, Linux, MacOS, etc.
- * Continuously adjustable angle from 0 to 105° over high quality unique torque hinges
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * High graphic resolution, up to 1920 x 1080 with 60Hz DDC, DDC2 and DDC2B

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables (8x KAB-102DVI) are not included with delivery. ****

**** Optional compatibility to HDMI devices with KAB-102-HDMI-DVI-USB ****

Specifications

Type		AW-1708HD-DVI
Computer Connection		8
CPU Port Selection		Front panel buttons/OSD menu
Cable Connectors	Keyboard / Mouse	3 x USB Type A (Front)
	Video	8 x DVI-I Socket (ATTENTION: only DVI-D cable usable)
LED's	Operation	1x green
	Num Lock	1x green
	Shift Lock	1x green
	Roll	1x green
	Port selection	8x green
LCD monitor	monitor	17,3" LCD monitor
	visible square	214.0 mm (H) * 380.0 mm (V)
	Resolution(max)	1920 x 1080 (DVI Single Link)
	Support Color	16.2 M / 262K colors
	White Luminance	300 cd/m ²
	contrast	700:1 (Typ)
	Back light	LED
	Pixel Pitch	0.264 mm (H) x 0.264 mm (V)
	LCD MTBF	50,000hours
	Input power	DC 12 V
Keyboards	keyboard	Standard with Num Lock, 104 signs
	Compatible IBM/AT	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.
	Emulation	PS/2 & USB
	Using life	>1,000,000 times
Mouse	X/Y resolution	1000dots/inch 40x40/mm
	Emulation	PS/2 & USB
	Os support	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF>60,000hours 25 °C
Housing		High performance steel (black), RAL 9005
Dimensions	without drawer handle	64,00 x 43,6 x 4,4cm (19" / 1U)
	with drawer handle	67,80 x 43,6 x 4,4cm (19" / 1U)
Rack installation depth		640mm - 1140mm (adjustable)
Weight / Weight incl. Packaging		12.9kg (incl. Mounting Kit) / 17.1kg
Operating/storage Temp		0° - 40°C / -20 - 60°C