



AS-7116ULS-IP

AS-7116ULS-IP is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. Connected by a 16-port VGA KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for sixteen VGA to VGA, PS/2 and USB connectors. A value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

Depth: 611mm

PARTICULARITY

This version has an integrated IP module (RJ45 Port), which realizes the function of "remote control".

FEATURES

- * Adjustable depth from 555 mm up to 900 mm tread depth
- * Sixteen VGA to VGA, PS/2 and USB connectors
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * high and clear resolution 1280 x 1024 (60Hz)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables (16x KD-KAB-102-4) are included with delivery. ****

Specifications

| Type | | AS-7116ULS-IP | |
|----------------------------------|-----------------|--|-------------------|
| Computer Connection (direct/max) | | 16 / 256 | |
| CPU Port Selection | | Front panel buttons / OSD menu / Hot Key | |
| IP Remote Control | | Yes | IP module KI-4101 |
| LCD monitor | Monitor type | 17" SXGA color TFT-LCD | |
| | Ratio | 4:3 | |
| | Visible square | 337.920(H) × 270.336(V) | |
| | Resolution(max) | 1280 x 1024 @ 60HZ | |
| | Support Color | 16.7M (RGB 6 bit + Hi_FRC) | |
| | contrast | 1000:1 (Typ) | |
| | Back light | LED | |
| | Pixel Pitch | 0.264 x 0.297mm | |
| | LCD MTBF | 100,000 hours | |
| | Input power | DC 12 V | |
| Connectors* | PC connectors | 16 x VGA DB15, Female (blue) | |
| | | 1 x USB for external mouse or keyboard (Front) | |
| | | 2 x USB for external mouse or keyboard (Rear) | |
| Keyboard | Keyboard | Standard 100keys (10 different languages for choose) | |
| | Compatibility | no limitations | |
| | Using life | >1,000,000 times | |
| Mouse | Type | Touch Pad | |
| | X/Y resolution | >1000dots/inch (40x40/mm) | |
| | Using life | >1,000,000 times | |
| Power | Power (AC) | ~100V-240V | |
| | Using life | MTBF >60,000hours 25 °C | |
| Housing | | Metal (black) | |
| Rail system | | Single Rail | |
| Gross weight | | 19.1 kg | |
| Dimensions (installation depth) | | 555 x 450 x 46 mm | |
| Dimensions (with handle) | | 611 x 450 x 46 mm | |
| Rack installation depth | | 555mm - 900mm (min/max adjustable) | |
| Operating / Storage Temp | | -10 - 50°C / -20 - 60°C | |
| Humidity | | 0 - 80% no condensation | |

* The needed system cables are included with delivery.