



## AS-7116TLS

AS-7116TLS is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. Connected by a 16-port Cat.5 KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for sixteen Cat.5 to VGA and USB connectors. A value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

**Depth: 611mm**

### FEATURES

- \* Adjustable depth from 555 mm up to 900 mm tread depth
- \* Sixteen Cat.5 to VGA and USB connectors
- \* compatible with the most KVM-Switches
- \* Support friendly external power supply
- \* Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- \* high and clear resolution 1280 x 1024 (60Hz)

### KEYBOARD VERSIONS

**Available with standard keyboard layouts:** German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

**Optional available against surcharge:** UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

\* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! \*

**\*\* The corresponding dongles (16x KD-DON-USB) are included with delivery. \*\***

## Specifications

Type		AS-7116TLS
Computer Connection (direct/max)		16 / 256
CPU Port Selection		Front panel buttons / OSD menu / Hot Key
IP Remote Control		No      --
LCD monitor	Monitor type	17" SXGA color TFT-LCD
	Ratio	4:3
	Visible square	337.920(H) × 270.336(V)
	Resolution(max)	1280 x 1024 @ 60HZ
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.264 x 0.297mm
	LCD MTBF	100,000 hours
	Input power	DC 12 V
Connectors	PC connectors	16 x RJ45 port
		1 x USB for external mouse or keyboard (Front)
		2 x USB for external mouse or keyboard (Rear)
Dongle*	Connector	1x RJ45 port
	Connector 2	1x VGA, 1x Kombi-USB
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatibility	no limitations
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal ( black )
Rail system		Single Rail
Gross weight		18.6 kg
Dimensions (installation depth)		555 x 450 x 46 mm
Dimensions (with handle)		611 x 450 x 46 mm
Rack installation depth		555mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C
Humidity		0 - 80% no condensation

\* The needed dongles are included with delivery.