







# AS-7116TLS-IP

AS-7116TLS-IP is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. Connected by a 16-port Cat.5 KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for sixteen Cat.5 to VGA and USB connectors. A value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

Depth: 611mm

#### **PARTICULARITY**

This version has an integrated IP module (RJ45 Port), which realizes the function of "remote control".

## **FEATURES**

- \* Adjustable depth from 555 mm up to 900 mm tread depth
- \* Sixteen Cat.5 to VGA and USB connectors
- \* compatible with the most KVM-Switches
- \* Support friendly external power supply
- \* Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- \* high and clear resolution 1280 x 1024 (60Hz)

### **KEYBOARD VERSIONS**

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

- \* ATTENTION: Delivery time for special layouts can vary! Please contact us!\*
- \*\* The corresponding dongles (16x KD-DON-USB) are included with delivery. \*\*

# **Specifications**

Туре		AS-7116TLS-IP	
Computer Connection (direct/max)		16 / 256	
CPU Port Selection		Front panel buttons / OSD menu / Hot Key	
IP Remote Control		Yes	KI-4101
LCD monitor	Monitor type	17" SXGA color TFT-LCD	
	Ratio	4:3	
	Visible square	337.920(H) × 270.336(V)	
	Resolution(max)	1280 x 1024 @ 60HZ	
	Support Color	16.7M (RGB 6 bit + Hi_FRC)	
	contrast	1000:1 (Тур)	
	Back light	LED	
	Pixel Pitch	0.264 x 0.297mm	
	LCD MTBF	100,000 hours	
	Input power	DC 12 V	
Connectors	PC connectors	16 x RJ45 port	
		1 x USB for external mouse or keyboard (Front)	
		2 x USB for external mouse or keyboard (Rear)	
Dongle*	Connector	1x RJ45 port	
	Connector 2	1x VGA, 1x Kombi-USB	
IP Port	Net Connection	1x RJ45 Port	
	Reset	1x LED	
	Default	1x LED	
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)	
	Compatibility	no limitations	
	Using life	>1,000,000 times	
Mouse	Туре	Touch Pad	
	X/Y resolution	>1000dots/inch (40x40/mm)	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF >60,000hours 25 °C	
Housing		Metal ( black )	
Rail system		Single Rail	
Gross weight		18.7 kg	
Dimensions (installation depth)		555 x 450 x 46 mm	
Dimensions (with handle)		611 x 450 x 46 mm	
Rack installation depth		555mm - 900mm (min/max adjustable)	
Operating / Storage Temp		-10 - 50°C / -20 - 60°C	
Humidity		0 - 80% no condensation	

 $<sup>\</sup>ensuremath{^{*}}$  The needed dongles are included with delivery.