



Front



Rear

## KS-3104

The KS-3104 is a rackmountable KVM Desktop Switch (Cat.5) which controls up to four servers via a single console and allows users to switch between the units via the buttons on the front panel or the hotkey configuration on the keyboard. It is the simplest and most convenient solution for multi-computer management.

Another advantage, next to the small, enclosure design, is the compact, sturdy metal housing, which is its most important feature. Because of the durable housing the total operating time is much longer then the TOT of comparable units built with synthetic material. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit. Depth 155.0mm

### FEATURES

- \* one USB console controls 4 computers/ servers via this switch
- \* keyboard and mouse simulation function built-in
- \* easy installation, no software required
- \* OS Compatibility: DOS, Windows series, Linux, Unix, etc.
- \* connection with computer via cable, AutoScan function to monitor computer operation
- \* superior video quality, 1600 x 900, (max. 1920 x 1200 @ 60Hz simulated)
- \* computer selection via front panel push buttons and hot keys
- \* hot pluggable to add or remove computers without powering down
- \* compact, sturdy, durable metal housing

**\*\* The corresponding dongles (4x KD-DON-USB) are included with delivery. \*\***

## Specifications

Type	KS-3104		
Computer Connection	direct	4	
	cascade (max.)	64	
CPU Port Selection	Front panel buttons / OSD menu / Hot Keys		
IP Remote Control	No	--	
Connector	Console Connectors	Video	1 x VGA DB15 Female (Blue)
		Keyboard	1 x USB Type A Female, 1 x PS2 Female (Purple)
		Mouse	1 x USB Type A Female, 1 x PS2 Female (Green)
	Computer Connectors	Terminal devices	4 x RJ45 port
		Dongle	1x RJ45 port
			1x VGA, 1x Kombi-USB
	Computer Selection Port		4 x Green
LED's	On Line		4 x Red
	IP Module Network Interface (optional)		1 x Green, 1 x Orange
Grafik	Resolution max.	1600 x 900 (max. 1920 x 1200 @ 60Hz simulated)	
Power	Power (AC)	DC 5V / 400mW	
	Using life	MTBF>60,000hours 25 °C	
Housing	Metal ( black )		
Dimensions	432 x 155 x 44mm		
Weight / Weight incl. packaging	1.9 kg / 2.75 kg		
Operating/storage Temp	-10°C - 50°C / -20°C - 60°C		