



AS-9104HD-DLS

AS-9104HD-DLS is an 18.5" FULL HD / LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant HD images and monitoring to unprecedented quality. AS-9104HD-DLS sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad and the integrated 4-port DVI KVM-switch are completing the external design. Four DVI and USB connectors allow the connection with four servers or PC's. The casing is easily installed and mountable with the included mounting kit. **Depth: 611mm**

PARTICULARITY

This version has the rare function of audio performance. Per audio output it is possible to connect a reproducing device, like a separate speaker or headphone. The reproducing device is not part of the scope of delivery.

FEATURES

- * Adjustable depth from 555 mm up to 900 mm tread depth
- * Four DVI, Audio and USB input connectors
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * High graphic resolution, up to 1920 x 1080 (Full HD)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables (4x KD-KAB-102DVI) are included with delivery. ****

**** Optional compatibility to HDMI devices with KAB-102-HDMI-DVI-USB ****

Specifications

Type		AS-9104HD-DLS
Computer Connection (direct/max)		4 / 64
CPU Port Selection		Front panel buttons / OSD menu / Hot Key
IP Remote Control		No --
LCD monitor	Monitor type	18.5 inch wide screen SXGA color TFT-LCD
	Ratio	16:9
	Visible square	409.8(H) x 230.4(V)mm
	Resolution(max)	1920 x 1080 (Full HD)
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)
	White Luminance	300 cd/m2 (Typ.)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.3 (per one triad) x 0.3
	LCD MTBF	100.000 hours
	Input power	DC 12 V
Connectors	PC connectors*	4 x DVI-D
		4 x Kombi-USB (Type B)
		4 x Kombi-Audio (microphone & speaker)
	Front	1 x USB for external mouse or keyboard
	Rear	2 x USB for external mouse or keyboard
		2 x 3,5mm Audio for speakers and microphone
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatibility	no limitations
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal (black)
Rail system		Single Rail
Gross weight		17.1 kg
Dimensions (installation depth)		555 x 450 x 46 mm
Dimensions (with handle)		611 x 450 x 46 mm
Rack installation depth		555mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C
Humidity		0 - 80% no condensation

* The needed system cables are included with delivery.