



## AS-3104DU-IP

The AS-3104DU-IP is a rackmountable KVM Desktop Switch (VGA) which controls up to four servers via a single console and allows users to switch between the units via the buttons on the front panel or the hotkey configuration on the keyboard. It is the simplest and most convenient solution for multi-computer management.

Another advantage, next to the small, enclosure design, is the compact, sturdy metal housing, which is its most important feature. Because of the durable housing the total operating time is much longer than the TOT of comparable units built with synthetic material. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit. Depth 155.0mm

### PARTICULARITY

This version has an integrated IP module (RJ45 Port), which realizes the function of "remote control".

### FEATURES

- \* one USB console controls 4 computers/ servers via this switch
- \* keyboard and mouse simulation function built-in
- \* easy installation, no software required
- \* OS Compatibility: DOS, Windows series, Linux, Unix, etc.
- \* connection with computer via cable, AutoScan function to monitor computer operation
- \* superior video quality, 1600 x 900, (max. 2048 x 1536 simulated)
- \* computer selection via front panel push buttons and hot keys
- \* hot pluggable to add or remove computers without powering down
- \* compact, sturdy, durable metal housing

**\*\* The corresponding cables (4x KD-KAB-102-4) are included with delivery. \*\***

## Specifications

Type		AS-3104DU-IP		
Computer Connection	direct	4		
	cascade (max.)	64		
CPU Port Selection		Front panel buttons / OSD menu / Hot Keys		
IP Remote Control		Yes	IP module KI-4101	
Connector	Console Connectors	Video	1 x VGA DB15 Female (Blue)	
		Keyboard	1 x USB Type A Female, 1 x PS2 Female (Purple)	
		Mouse	1 x USB Type A Female, 1 x PS2 Female (Green)	
	Computer Connectors	Video/Keyboard/Mouse	4 x VGA DB15 Female (Blue)	
	Power		1 x DC	
	IP Module Network Interface (optional)		1 x RJ45	
IP Port	Net Connection	1x RJ45 Port		
	Reset	1x LED		
	Default	1x LED		
LED's	Computer Selection Port		4 x Green	
	On Line		4 x Red	
	IP Module Network Interface (optional)		1 x Green, 1 x Orange	
Grafik	Resolution max.	1600 x 900 (max. 2048 x 1536 simulated)		
Power	Power (AC)	DC 5V / 400mW		
	Using life	MTBF>60,000hours 25 °C		
Housing		Metal ( black )		
Dimensions		432 x 155 x 44mm		
Weight / Weight incl. packaging		2.1 kg / 3.0 kg		
Operating/storage Temp		-10°C - 50°C / -20°C - 60°C		