



KI-4101

The KI-4101 is the optional IP module for LANBE's AS- & KS-series. It is compatible to all devices of the AS- & KS-series which are built with an optional slot for an IP Interface. KI-4101 realizes the „remote control“ function and gives users the possibility for global access to the connected KVM console or KVM switch. An important innovation, compared with the former model, is that it supports remote resolutions up to 1920 x 1080 at 60Hz.

The global access also ensured when the connected KVM drawer is closed, because of the fact that the IP module and the connected switch stay active. This IP module is the easiest way for a successful and professional multi-computer-management.

FEATURES

- * superior remote video quality up to 1920 x 1080 at 60Hz
- * operator-friendly user interface
- * high reliability

Specification

Product number		KI-4101
Control Port	Keyboard	RJ45 port x 1
	Mouse	
	Video	
Input Port	Keyboard	HD15F/integration port x 1
	Mouse	(VGA video, USB mouse/keyboard, PS/2mouse/keyboard)
	Video	
Power Supply Port		DC-5.5*2.1
Reset		Network Re-connect
Default		Initialize IP module default IP address, administrator name and initial password
LED Indicator		Power indicator
Max Resolution		1920 x 1080@60Hz
Power Supply		DC 12V 1000mA
Operating Temperature		0-50°C
Storage Temperature		-20 -60
Housing		metal
Weight		0.5KG
Dimensions(L x W x H)		162*78*30mm