



## AS-9108DA

The AS-9108DA is a rackmountable DVI KVM switch which controls up to eight servers via a single console and allows users to switch between the units via the buttons on the front panel or the hotkey configuration on the keyboard. It is the simplest and most convenient solution for multi-computer management.

Another advantage, next to the small, enclosure design, is the compact, sturdy metal housing, which is its most important feature. Because of the durable housing the total operating time is much longer than the TOT of comparable units built with synthetic material. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit. Depth 155.0mm

### FEATURES

- \* one USB console controls 8 computers/ servers via this switch
- \* keyboard and mouse simulation function built-in
- \* easy installation, no software required
- \* OS Compatibility: DOS, Windows series, Linux, Unix, etc.
- \* connection with computer via cable, AutoScan function to monitor computer operation
- \* superior video quality, 1920 x 1200 @ 60Hz (max.)
- \* computer selection via front panel push buttons and hot keys
- \* hot pluggable to add or remove computers without powering down
- \* compact, sturdy, durable metal housing

**\*\* The corresponding cables (8x KD-KAB-102-DVI) are included with delivery. \*\***

## Specifications

Type		AS-9108DA	
Computer connections	direct	8	
	cascade (max.)	128	
CPU Port Selection		Druckschalter Frontseite / OSD Menü / Hot Keys	
IP Remote Control		--	--
Connectors	Console connectors	Video	1 x DVI-D
		Keyboard	1 x USB Type A Female, 1 x PS2 Female (purple)
		Mouse	1 x USB Type A Female, 1 x PS2 Female (green)
		Audio / microphone	1 x Mini Stereo (black)
	Computer connectors	Video/keyboard/mouse	8 x DVI-D, 8 x USB Type B
		Audio	8x Mini Stereo (green)
		Microphone	8x Mini Stereo (red)
	Power		1 x DC
LEDs	Computer Selection Port		8 x green
	On Line		8 x red
Graphics	Resolution (max)	1920 x 1200 @ 60Hz (max.)	
Power	Power (AC)	DC 9V / 1000mA	
	Using life	MTBF >60,000 hours at 25 °C	
Housing		metal (black)	
Dimensions		432 x 155 x 44mm	
Weight / Weight incl. packaging		1.9 kg / 3.0 kg	
Operating/storage temp		-10°C - 50°C / -20°C - 60°C	
Humidity		0 - 80%	