





AS-9116HD-HLS

AS-9116HD-HLS is an 18.5" FULL HD / LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant Full HD images and monitoring to unprecedented quality. AS-9116HD-HLS sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad and the integrated 16-port HDMI KVM-switch are completing the external design. Sixteen HDMI and USB connectors allow the connection with sixteen servers or PC's. The casing is easily installed and mountable with the included mounting kit.

Depth: 611mm

FEATURES

- * Adjustable depth from 555 mm up to 900 mm tread depth
- * Sixteen HDMI and USB input connectors
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * High graphic resolution, up to 1920 x 1080 (Full HD)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

- * ATTENTION: Delivery time for special layouts can vary! Please contact us! *
- ** The corresponding cables (16x KD-KAB-102HDMI) are included with delivery. **

Specifications

Туре		AS-9116HD-HLS
Computer Connection (direct/max)		16 / 256
CPU Port Selection		Front panel buttons / OSD menu / Hot Key
IP Remote Control		No
LCD monitor	Monitor type	18.5 inch wide screen SXGA color TFT-LCD
	Ratio	16:9
	Visible square	409.8(H) x 230.4(V)mm
	Resolution(max)	1920 x 1080 (Full HD)
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)
	White Luminance	300 cd/m2 (Typ.)
	contrast	1000:1 (Тур)
	Back light	LED
	Pixel Pitch	0.3 (per one triad) x 0.3
	LCD MTBF	100.000 hours
	Input power	DC 12 V
Connectors	PC connectors*	16 x HDMI
		16 x Kombi-USB (Type B)
	Front	1 x USB for external mouse or keyboard
	Rear	2 x USB for external mouse or keyboard
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatibility	no limitations
	Using life	>1,000,000 times
Mouse	Туре	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal (black)
Rail system		Single Rail
Gross weight		18.4 kg
Dimensions (installation depth)		555 x 450 x 46 mm
Dimensions (with handle)		611 x 450 x 46 mm
Rack installation depth		555mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C
Humidity		0 - 80% no condensation

 $[\]ensuremath{^{*}}$ The needed system cables are included with delivery.