



AS-9108HLS

AS-9108HLS is a single rail 19" Monitor, Keyboard-Drawer with LED Backlight. Connected by an 8-port HDMI KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for eight HDMI and USB and a value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

Depth: 611mm

FEATURES

- * Adjustable depth from 555 mm up to 900 mm tread depth
- * Eight HDMI and USB Input connectors
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * 19" LED screen with high brightness, high and clear, high, native resolution of 1366 x 768 (60Hz)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables (8x KD-KAB-102HDMI) are included with delivery. ****

Specifications

Type		AS-9108HLS
Computer Connection (direct/max)		8 / 128
Port Selection		Front panel buttons / OSD menu / Hot Key
IP Remote Control		No --
LCD monitor	Monitor type	18.5 inch SXGA color TFT-LCD
	Ratio	16:9
	Visible square	409.8(H) x 230.4(V)mm
	Resolution(max)	1366 x 768 (native) 60Hz
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)
	White Luminance	250 cd/m2 (Typ.)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.3 (per one triad) x 0.3
	LCD MTBF	50,000 hours
	Input power	DC 12 V
Connectors	PC connectors	8 x HDMI
		8 x Kombi-USB (Type B)
	Front	1 x USB for external mouse or keyboard
	Rear	2 x USB for external mouse or keyboard
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatibility	no limitations
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal (black)
Rail system		Single Rail
Gross weight		17.3 kg
Dimensions (installation depth)		555 x 450 x 46 mm
Dimensions (with handle)		611 x 450 x 46 mm
Rack installation depth		555mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C
Humidity		0 - 80% no condensation

* The needed system cables are included with delivery.