



AS-7104DLS

AS-7104DLS is a single rail 17" Monitor, Keyboard-Drawer with LED Backlight. Connected by a 4-port DVI KVM switch to the terminal, it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for four DVI and USB and a value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit.

Depth: 611mm

PARTICULARITY

This version has the rare function of audio performance. Per audio output it is possible to connect a reproducing device, like a separate speaker or headphone. The reproducing device is not part of the scope of delivery.

FEATURES

- * Adjustable depth from 555 mm up to 900 mm tread depth
- * Four DVI, Audio and USB Input connectors
- * compatible with the most KVM-Switches
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * high and clear resolution 1280 x 1024 (60Hz)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables (4x KD-KAB-102DVI) are included with delivery. ****

**** Optional compatibility to HDMI devices with KAB-102-HDMI-DVI-USB ****

Specifications

Type		AS-7104DLS
Computer Connection (direct/max)		4 / 64
CPU Port Selection		Front panel buttons / OSD menu / Hot Key
IP Remote Control		No --
LCD monitor	Monitor type	17" SXGA color TFT-LCD
	Ratio	4:3
	Visible square	337.920(H) × 270.336(V)
	Resolution(max)	1280 x 1024 @ 60HZ
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.264 x 0.297mm
	LCD MTBF	100,000 hours
	Input power	DC 12 V
Connectors	PC connectors*	4 x DVI-D
		4 x Kombi-USB (Type B)
		4 x Kombi-Audio (microphone & speaker)
	Front	1 x USB for external mouse or keyboard
	Rear	2 x USB for external mouse or keyboard
		2 x 3,5mm Audio for speakers and microphone
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatible IBM/AT	no limitations
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal (black)
Rail system		Single Rail
Gross weight		17.8 kg
Dimensions (installation depth)		555 x 450 x 46 mm
Dimensions (with handle)		611 x 450 x 46 mm
Rack installation depth		555mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C
Humidity		0 - 80% no condensation

* The needed system cables are included with delivery.