



AS-9100DLS

AS-9100DLS is a single rail 18.5" Monitor, Keyboard-Drawer with LED Backlight. Connected by a single port DVI KVM switch to the terminal (supplied DB37-system cable), it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for DVI, PS/2 and USB and a value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit. **Depth: 410mm** (without handle)

FEATURES

- * Front LCD Console + DB 37pins cable in **short total depth 410mm**, supports PS.2/USB
- * Can be connected with different KVM modules, for example with 4/8/16 ports (VGA/CAT5/DVI/HDMI)
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * an USB 1.1 port on the frontside, for external mouse or keyboard
- * high and clear resolution 1366 x 768 (60Hz)
- * Support friendly external power supply

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables are included with delivery. ****

Specifications

Type		AS-9100DLS	
Computer Connection (direct/max)		1	
CPU Port Selection		--	
IP Remote Control		No	--
LCD monitor	Monitor type	18.5 inch SXGA color TFT-LCD	
	Ratio	16:9	
	Visible square	409.8(H) x 230.4(V)mm	
	Resolution(max)	1366 x 768 (native) 60Hz	
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)	
	White Luminance	250 cd/m2 (Typ.)	
	contrast	1000:1 (Typ)	
	Back light	LED	
	Pixel Pitch	0.3 (per one triad) x 0.3	
	LCD MTBF	50,000 hours	
	Input power	DC 12 V	
Connectors	DB 37pin Rear*	1x DVI-D	
		1x Kombi-USB	
		2 x PS/2 female (purple/green)	
	USB Front	1 x USB for external mouse or keyboard	
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)	
	Compatible IBM/AT	Win Series/Server 2008/Server 2013/Linux, MacOS, etc.	
	Using life	>1,000,000 times	
Mouse	Type	Touch Pad	
	X/Y resolution	>1000dots/inch (40x40/mm)	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF >60,000hours 25 °C	
Housing		Metal (black)	
Rail system		Single Rail	
Gross weight		14.5 kg	
Dimensions (installation depth)		407.5 x 450 x 46mm	
Dimensions (with handle)		462.6 x 450 x 46mm	
Rack installation depth		410mm - 900mm (min/max adjustable)	
Operating / Storage Temp		-10 - 50°C / -20 - 60°C	
Humidity		0 - 80% no condensation	

* The needed DB37-system cable is included with delivery.