



## AS-9104HD-TLS-IP

AS-9104HD-TLS-IP is an 18.5" FULL HD / LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant HD images and monitoring to unprecedented quality. AS-9104HD-TLS-IP sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad and the integrated 4-port Cat.5 KVM-switch are completing the external design. Four Cat.5 to VGA and USB connectors allow the connection with four servers or PC's. The casing is easily installed and mountable with the included mounting kit. **Depth: 611mm**

### PARTICULARITY

This version has an integrated IP module (RJ45 Port), which realizes the function of "remote control".

### FEATURES

- \* Adjustable depth from 555 mm up to 900 mm tread depth
- \* Four Cat.5 to VGA and USB connectors
- \* compatible with the most KVM-Switches
- \* Support friendly external power supply
- \* Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- \* High graphic resolution, up to 1920 x 1080 (Full HD)

### KEYBOARD VERSIONS

**Available with standard keyboard layouts:** German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

**Optional available against surcharge:** UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

\* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! \*

**\*\* The corresponding dongles (4x KD-DON-USB) are included with delivery. \*\***

## Specifications

Type		AS-9104HD-TLS-IP	
Computer Connection (direct/max)		4 / 64	
CPU Port Selection		Front panel buttons / OSD menu	
IP Remote Control		Yes	IP module KI-4101
LCD monitor	Monitor type	18.5 inch wide screen SXGA color TFT-LCD	
	Ratio	16:9	
	Visible square	409.8(H) x 230.4(V)mm	
	Resolution(max)	1920 x 1080 (Full HD)	
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)	
	White Luminance	300 cd/m2 (Typ.)	
	contrast	1000:1 (Typ)	
	Back light	LED	
	Pixel Pitch	0.3 (per one triad) x 0.3	
	LCD MTBF	100.000 hours	
	Input power	DC 12 V	
Connectors	PC connectors	4 x RJ45 port	
		1 x USB for external mouse or keyboard (Front)	
		2 x USB for external mouse or keyboard (Rear)	
Dongle*	Connector	1x RJ45 port	
	Connector 2	1x VGA, 1x Kombi-USB	
IP Port	Net Connection	1x RJ45 Port	
	Reset	1x LED	
	Default	1x LED	
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)	
	Compatible IBM/AT	no limitations	
	Using life	>1,000,000 times	
Mouse	Type	Touch Pad	
	X/Y resolution	>1000dots/inch (40x40/mm)	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF >60,000hours 25 °C	
Housing		Metal ( black )	
Rail system		Single Rail	
Gross weight		17.2 kg	
Dimensions (installation depth)		555 x 450 x 46 mm	
Dimensions (with handle)		611 x 450 x 46 mm	
Rack installation depth		555mm - 900mm (min/max adjustable)	
Operating / Storage Temp		-10 - 50°C / -20 - 60°C	
Humidity		0 - 80% no condensation	

\* The needed dongles are included with delivery.