



## AS-9100HLS

AS-9100HLS is a single rail 19" Monitor, Keyboard-Drawer with LED Backlight. Connected by a single port HDMI KVM switch to the terminal (supplied DB37-system cable), it is a compact monitor-, keyboard- & mouse-solution for your server rack. It has connections for HDMI, PS/2 and USB and a value keyboard with number block and the integrated touchpad are completing the external design. It is easily to install and mountable with the included mounting kit. **Depth: 410mm** (without handle)

### FEATURES

- \* Front LCD Console + DB 37pins cable in **short total depth 410mm**, supports PS.2/USB
- \* Can be connected with different KVM modules, for example with 4/8/16 ports (VGA/CAT5/DVI/HDMI)
- \* Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- \* an USB 1.1 port on the frontside, for external mouse or keyboard
- \* high and clear resolution 1366 x 768 (60Hz)
- \* Support friendly external power supply

### KEYBOARD VERSIONS

**Available with standard keyboard layouts:** German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

**Optional available against surcharge:** UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

\* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! \*

**\*\* The corresponding cables are included with delivery. \*\***

## Specifications

Type		AS-9100HLS
Computer Connection (direct/max)		1
CPU Port Selection		--
IP Remote Control		No --
LCD monitor	Monitor type	18.5 inch SXGA color TFT-LCD
	Ratio	16:9
	Visible square	409.8(H) x 230.4(V)mm
	Resolution(max)	1366 x 768 (native) 60Hz
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)
	White Luminance	250 cd/m2 (Typ.)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.3 (per one triad) x 0.3
	LCD MTBF	50,000 hours
	Input power	DC 12 V
Connectors	DB 37pin Rear*	1x HDMI
		1 x Kombi-USB
		2 x PS/2 female (purple, green)
	USB Front	1 x USB for external mouse or keyboard
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)
	Compatible IBM/AT	no limitations
	Using life	>1,000,000 times
Mouse	Type	Touch Pad
	X/Y resolution	>1000dots/inch (40x40/mm)
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF >60,000hours 25 °C
Housing		Metal ( black )
Rail system		Single Rail
Gross weight		14.5 kg
Dimensions (installation depth)		407.5 x 450 x 46mm
Dimensions (with handle)		462.6 x 450 x 46mm
Rack installation depth		410mm - 900mm (min/max adjustable)
Operating / Storage Temp		-10 - 50°C / -20 - 60°C
Humidity		0 - 80% no condensation

\* The needed DB37-system cable is included with delivery.