



AS-9100HD-HLS

AS-9100HD-HLS is an 18.5" FULL HD / LCD-Monitor, Keyboard-Drawer with LED Backlight. The new equipment ensures brilliant HD images and monitoring to unprecedented quality. AS-9100HD-HLS sets a new standard in picture quality inside the server room. A value keyboard with number block and touchpad and the integrated HDMI, PS/2 and USB connectors are completing the external design. The casing is easily installed and mountable with the included mounting kit. **Depth 410mm** (without handle)

FEATURES

- * FullHD DVI console + DB 37pins cable in short total length of **410mm**
- * HDMI Input, PS/2 or USB for Keyboard und Touchpad/Mouse
- * Adjustable depth from 410mm up to 900mm tread depth
- * Can be connected with different KVM modules, for example with 4/8/16 ports (VGA/CAT5/DVI/HDMI)
- * Support friendly external power supply
- * Perfect keyboard / mouse emulation for safe function on all computers and operating systems
- * High graphic resolution, up to 1920 x 1080 (Full HD)

KEYBOARD VERSIONS

Available with standard keyboard layouts: German (DE), US-English (US), French (FR), Spanish (SP), Italian (IT). Swiss / German (CH)

Optional available against surcharge: UK-English (UK), Turkish (TK), Russian (RU), swedish / finnish (SWE/FI) and multilingual arabian / US-english (AR / US)

* **ATTENTION:** Delivery time for special layouts can vary ! Please contact us ! *

**** The corresponding cables are included with delivery. ****

Specifications

Type		AS-9100HD-HLS	
Computer Connection (direct/max)		1	
CPU Port Selection		--	
IP Remote Control		No	--
LCD monitor	Monitor type	18.5 inch wide screen SXGA color TFT-LCD	
	Ratio	16:9	
	Visible square	409.8(H) x 230.4(V)mm	
	Resolution(max)	1920 x 1080 (Full HD)	
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)	
	White Luminance	300 cd/m2 (Typ.)	
	contrast	1000:1 (Typ)	
	Back light	LED	
	Pixel Pitch	0.3 (per one triad) x 0.3	
	LCD MTBF	100.000 hours	
	Input power	DC 12 V	
Connectors	DB 37pin Rear*	1x HDMI	
		1 x PS/2 female (purple), 1 x Kombi-USB	
		1 x PS/2 female (green), 1 x Kombi-USB	
	USB Front	1 x USB (front) for external mouse or keyboard	
Keyboard	Keyboard	Standard 100keys (10 different languages for choose)	
	Compatible IBM/AT	no limitations	
	Using life	>1,000,000 times	
Mouse	Type	Touch Pad	
	X/Y resolution	>1000dots/inch (40x40/mm)	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF >60,000hours 25 °C	
Housing		Metal (black)	
Rail system		Single Rail	
Gross weight		14.6 kg	
Dimensions (installation depth)		407.5 x 450 x 46mm	
Dimensions (with handle)		462.6 x 450 x 46mm	
Rack installation depth		410mm - 900mm (min/max adjustable)	
Operating / Storage Temp		-10 - 50°C / -20 - 60°C	
Humidity		0 - 80% no condensation	

* The needed DB37-system cable is included with delivery.