



AS-9108HA

The AS-9108HA is a rackmountable HDMI KVM switch which controls up to eight servers via a single console and allows users to switch between the units via the buttons on the front panel or the integrated OSD menu. It is the simplest and most convenient solution for multi-computer management.

Another advantage, next to the small, enclosure design, is the compact, sturdy metal housing, which is its most important feature. Because of the durable housing the total operating time is much longer than the TOT of comparable units built with synthetic material. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit. Depth 155.0mm

FEATURES

- * superior video quality **with 4K x 2K Ultra HD resolution**
- * supports 480i, 480p, 720p, 1080i, 1080p, 2160i and 2160p
- * one USB console controls 8 computers/ servers via this switch
- * keyboard and mouse simulation function built-in
- * easy installation, no software required
- * OS Compatibility: DOS, Windows series, Linux, Unix, etc.
- * connection with computer via cable, AutoScan function to monitor computer operation
- * computer selection via front panel push buttons or the integrated OSD menu
- * hot pluggable to add or remove computers without powering down
- * compact, sturdy, durable metal housing

**** The corresponding cables (8x KD-KAB-102-HDMI) are included with delivery. ****

Specifications

Type		AS-9108HA	
Computer connections	direct	8	
CPU Port Selection		Front panel switches / OSD menu	
IP Remote Control		--	--
Connectors	Console connectors	Video	1 x HDMI Female
		Keyboard	1 x USB Type A Female
		Mouse	1 x USB Type A Female
	Computer connectors	Video	8 x HDMI Female
		Keyboard / Mouse	8 x USB TYPE B Female
	Power supply		1 x DC Jack
LEDs	Computer Selection Port		8 x green
	Online		8 x red
Graphics	Resolution (max)	4K x 2K @ 60Hz	
		supports 480i, 480p, 720p, 1080i, 1080p, 2160i and 2160p	
Scanintervall		3, 5, 10, 15, 20, 30, 40, 60 sec (Default 3 sec)	
Power	Power supply	DC 9V / 1000mA	
	Using life	MTBF >60,000 hours at 25 °C	
Housing		metal (black)	
Dimensions		432 x 155 x 44mm	
Weight / Weight incl. packaging		1.8 kg / 3.0 kg	
Operating/storage temp		0°C - 50°C / -20°C - 60°C	
Humidity		0 - 80% no condensation	