



AS-9116HA

The AS-9116HA is a rackmountable HDMI KVM switch which controls up to sixteen servers via a single console and allows users to switch between the units via the buttons on the front panel or the integrated OSD menu. It is the simplest and most convenient solution for multi-computer management.

Another advantage, next to the small, enclosure design, is the compact, sturdy metal housing, which is its most important feature. Because of the durable housing the total operating time is much longer than the TOT of comparable units built with synthetic material. The housing conforms the 1U standard, is easily installed and mountable with the included mounting kit. Depth 155.0mm

FEATURES

- * superior video quality **with 4K X 2K Ultra HD resolution**
- * supports 480i, 480p, 720p, 1080i, 1080p, 2106i and 2160p
- * one USB console controls 16 computers / servers via this switch
- * keyboard and mouse simulation function built-in
- * easy installation, no software required
- * OS Compatibility: DOS, Windows series, Linux, Unix, etc.
- * connection with computer via cable, AutoScan function to monitor computer operation
- * computer selection via front panel push buttons or the integrated OSD menu
- * hot pluggable to add or remove computers without powering down
- * compact, sturdy, durable metal housing

**** The corresponding cables (16x KD-KAB-102-HDMI) are included with delivery. ****

Specifications

| Type | | AS-9116HA | |
|---------------------------------|-------------------------|--|------------------------|
| Computer connections | direct | 16 | |
| CPU port selection | | Front panel switches / OSD menu | |
| IP Remote Control | | -- | -- |
| Connectors | Console connectors | Video | 1 x HDMI Female |
| | | Keyboard | 1 x USB Type A Female |
| | | Mouse | 1 x USB Type A Female |
| | Computer connectors | Video | 16 x HDMI Female |
| | | Keyboard / Mouse | 16 x USB TYPE B Female |
| | Power supply | | 1 x DC Jack |
| LEDs | Computer Selection Port | | 16 x green |
| | Online | | 16 x red |
| Graphics | Resolution (max) | 4K x 2K @ 60Hz | |
| | | supports 480i, 480p, 720p, 1080i, 1080p, 2106i and 2160p | |
| Scanintervall | | 3, 5, 10, 15, 20, 30, 40, 60 sec (Default 3 sec) | |
| Power | Power supply | DC 9V / 1000mA | |
| | Using life | MTBF >60,000 hours at 25 °C | |
| Housing | | metal (black) | |
| Dimensions | | 432 x 155 x 44mm | |
| Weight / Weight incl. packaging | | 1.8 kg / 3.0 kg | |
| Operating/storage temp | | 0°C - 50°C / -20°C - 60°C | |
| Humidity | | 0 - 80% no condensation | |